



NIRMALA NIKETAN INSTITUTE'S
COLLEGE OF HOME SCIENCE,
NIRMALA NIKETAN

Affiliated to the University of Mumbai
NAAC Accredited 'A+' Grade

49, New Marine Lines, Churchgate, Mumbai - 400 020. ☎ 2207 6503 / 2200 7544
Email: principal@nnchsc.edu.in / office@nnchsc.edu.in Web.: www.nirmalaniketan.com

28th Aug 24

Sub: Inviting Quotations for Carpentry work in Classrooms and Exam Room

Respected Sir/Madam,

We intend to get **Carpentry work done in Classrooms and Exam Room**. We are looking for **vendors who can do the work** with the given specifications of the wooden work. We invite you to send your most competitive quotations for the same.

If your prices and terms are favourable, as per our specifications, we shall consider giving the contract to you for the **Carpentry work in Classrooms and Exam Room**.

Please provide us the quote for the following detailed below:

Sr no	Description	No's	Unit	Total qty	Rate	Amount
1	Installation of a single Leaf Door with a thickness of 60 mm Thick single piece Wooden Door. with 1 handel lock, 2 Tower bolts of 6 inches. Application of 1 coat of primer and two coats of OBD paint as per colour suggested by Consultant. • Size (6' 6" x 3' 9")	3	SQFT	76.05		
2	Installation of a Double Leaf Door with a thickness of 60 mm Thick single piece Wooden Door. with 1 handel lock, 2 Tower bolts of 6 inches. Application of 1 coat of primer and two coats of OBD paint as per colour suggested by Consultant. • Size (6' 6" x 4' 6")	4	SQFT	117		
3	Exam Room upgradation Installation of 2 tables with following details • size of top (18 inches x 200 inches) • partition and three nos of drawers with knobs and all inclusive • 1 mm sunmica as selected by client.	2	SQFT	64		
4	Installation of classroom desk • Making new desk of size 18 inches x 48 inches with 1 mm Glossy sunmica, consider suitable support and 4 legs of size 50 mm x 50 mm thickness.	12	No's	72		
	Total (Excluding Taxes)					


Estimated Cost: Rs 3.45 Lakhs (including GST)

Kindly also send details on the mode of payment and terms and conditions (if any). Please give the reference of our website on your quotation and address the quotation to **“The Principal, College of Home Science Nirmala Niketan, Mumbai – 400020”**.

Kindly mail the softcopy to principal@nnchsc.edu.in and admin@nnchsc.edu.in by 31st Aug 2024, 1 pm, and courier the quotation in a sealed envelope to College of Home Science Nirmala Niketan, 49, New Marine Lines Mumbai 400020, by 31st Aug 2024 by 5 pm.
We hope to hear from you soon regarding this quote request.

We also look forward to a long-standing business relationship with you if this transaction is a success.

Thanking You,
Yours Sincerely,

 23/8/2024

In Charge Principal
Prof. Dr. Vishaka Karnad

Wooden Work Specifications
Type and make of materials to be used

Sr. no.	Item Description	Approved Brands / Manufacturers
1	Plywood Marine ISI 710 (BWP)	Century & if not available then equivalent with Clients/Architect approval.
2	Plain particle board	Decoboard, Nuwud, Archidply, Nova Teak super by Indian Plywood Mfg. Co. -ISI Approved grade
3	Partition Frame Work	Teakwood, Wood guard with black japan on it
4	Exposed Wood	CP Teakwood, BTC wood, Agrowood, Rubberwood
6	Laminates 1mm & 1.25 mm	Royal Touch (Luxury laminates) or equivalent
7	Drawer channels	Earl Bihari, Hettich brand or equivalent
8	Keyboard/ Hardware	EBCO, Hettich or equivalent
9	Soft Board	Alfa 44 Pravin Kumar or equivalent
10	Screws	Nettlefold, GKW or equivalent
11	Hardware (Imported)	Dorma, Hafel or equivalent
12	Adhesives	Fevicol SH & SR, Movicol HV of Mafatlal, Araldite of ciba Geigy, Vemicol, Parcol, Feviquick or equivalent
14	Locks	Godrej or equivalent
15	Handles	Haffel or equivalent
16	Wood Preservative	Bison by British paints, Woodguard, Termiseal or equivalent
18	Chairs	Godrej or equivalent
19	Blinds	Vista, Innovative or equivalent
25	1mm Glossy sunmica	Century brand.
26	Tower Bolts	Haffel or equivalent
29	Latch and knobs	Godrej or equivalent

General Specifications of the Work:

1. Painting of wooden doors:

- Sand the existing paint on door with a sanding paper no. 120
- Apply 1st coat of oil-based primer of Asian paints and leave it for drying overnight
- Apply 1st coat of oil-based paint of Asian paints and leave it for 6-8 hours for drying.
- After that apply the 2nd finishing coat of oil-based paint.
- Paint any decorative moulding first, and then paint the interior of the panels.

2. Installation of Wooden Doors.

- The existing doors should be removed after causing minimum damage to the existing wall.
- The wood and minimum and maximum moisture content shall be as per IS 12896:1990.
- All members of Doors shall be exactly at right angle and without any wrap or bow.
- Wood used shall be solid and strong wood and shall be bought from a reputed supplier.
- Fixture shall be used of Stainless steel.
- Door handles, Latch and knobs should be used of Godrej brand.
- Each door shall be provided with a Lock of Godrej brand.

3. General Specifications for all wood work:

- All internal woodwork shall be treated with anti-termite preservative.
- All internal framework shall be of teak wood unless otherwise specified.
- All exposed edges of plywood /blockboard shall be finished with 1mm thick Laminate.
- All plywood/blockboard shall be of marine grade/quality unless otherwise specified.
- Drawer bottom, shelves bottom and bottom surface of table top shall be finished with approved French polish minimum 2 coats etc unless specified.
- Irrespective of thickness mentioned in the drawings, laminate shall be of following thickness as mentioned below:
 - a) 1.25mm thick Laminate :- Horizontal Surface
 - b) 1.0mm thick Laminate :- Vertical Surface
 - c) 1mm thick Laminate :- On internal visible surface except bottom surface of table top, shelf bottom and drawer bottom.
 - d) 1.0 mm thick Laminate on all edges of Counters, Drawers, Storage shutters, Shelves.
- Laminations of various thickness shall be of Royal Touch (Luxury Laminates) or equivalent manufacturer.

4. General specification for locks, hinges and other fixtures used in Plywood:

- Shelves - 3/4" thick. marine plywood with all exposed edges in laminate positioned to accommodate vertical files, removable and supported on pins.
- Shutters - made out of 3/4" thick marine ply . All external surfaces, front, sides, all exposed edges shall have 1.0 mm thick. Laminate of approved make and colours complete as per instructions at site.
- Hinges - Each shutter shall have 4" long black oxidised brass butt or L hinges. Minimum 4 nos. hinges for Full height Storage and 2 nos. hinges for Low height Storage.
- Bolts - Flush tower bolts on the inside at top and bottom to the required shutters only - other shutters will have magnetic catch fixed top and bottom.
- Locks - Of approved make 4 - lever brass body dead lock with S.S. Key master key for groups as required.
- Handles - 6" ht. sunken brush steel of approved make.
- Skirting - 4" x 3/4" thick marine plywood for skirting.
- Finishing - All external visible surfaces finish with 1.0 mm thk laminate. Inside visible surfaces finished in 1 mm laminate. All internal woodwork to be hand polished. Backing marine ply will have anti-termite treatment & G. I. sheet.